

# VILLA ROOT BARRIER, INC.

## ALUMINUM LANDSCAPE EDGING

### SPECIFICATIONS ALUMINUM LANDSCAPE EDGING

SIZE (ALL 16' LENGTHS)	PRODUCT APPLICATION
1/8" x 4" 3.2mm	Used primarily for residential or light commercial applications. Works best where flowing curves are needed.
3/16" x 4" 4.8mm	Used primarily for commercial, industrial, and institutional facilities. Works well for both long and straight runs and curves.
1/8" x 5.5" 3.2mm	Used primarily for residential or light commercial applications where the planting beds may require the additional depth.
3/16" x 5.5" 4.8mm	Used primarily for commercial, industrial, and institutional facilities where the additional depth and strength is needed.
STAKES 1.5" X 11.5" = 3.8mm X 292mm	

### Easy Installation

- Forming of bedlines is simplified.
- 90 degree corners and irregular shapes are easily obtained without special connectors.
- Stake adapter eliminates problems using cut pieces of edging where no locking mechanism exists.
- Stake adapter allows placing stake at any location. Grooves in stakes hold edging firmly in the ground. Superior locking system.
- 16' section includes (5) five stakes and (1) one stake adapter.

Edging is to lock together with no offset or overlap at the joints. Install with 5 stakes per 16' section. Stakes are to be installed 1/2" (12.7mm) below top edge, out of view. At all start and stop points, install end stake adapters to properly secure these critical areas.

## DURA EDGE®

### SPECIFICATIONS

#### PAINTED STEEL OR GALVANIZED STEEL

<b>14 ga</b> (.070 - .075")	Lightweight, low cost residential or commercial edging installs quickly and easily allowing imaginative free form design.
<b>12 ga</b> (.10, .105")	Possesses the durable, heavy duty characteristics of 1/8" edging while providing the lightweight, conventional installation properties similar to the 14 ga in the shorter 10' lengths.
<b>1/8"</b> (.12 - .125")	Versatile, lightweight commercial edging. Providing economical durability and uniformity to flower beds and ground cover separation.
<b>3/16"</b> (.182 - .188")	General purpose commercial edging, most commonly used in walkways, driveways and perimeter strips providing strength and continuity to all landscape designs.
<b>1/4"</b> (.20 - .25")	Heavy duty edging for use where straight lines are essential. Ideal for rock and gravel retention on pathways and where erosion control of blacktop driveways and parking lots is required.

### Steel Landscape Edging

SIZE	14ga	12ga	1/8"	3/16"	1/4"
DEPTH	4",6"	4"	4"	4"	5"
LENGTH	8',10'	10'	16'	16'	16'
ACTUAL COVERAGE					
8FT	7' - 4"				
10 FT	9'-4"	9'-4"	-	-	-
16 FT	-	-	15'-4"	15'-4"	15'-4"
NUMBER OF STAKES (per piece)					
8FT	4	-	-	-	-
10 FT	4	4			
16FT	-	-	6	6	7
STAKE DEPTH	12",14"	12",14"	12",14"	16"	16"
APPROX. WEIGHT (lbs. including stakes)					
8 FT	1.3/ft 1.9/ft	-	-	-	-
10 FT	1.3/ft 1.9/ft	1.7/ft	-	-	-
16 FT	-	-	2.0/ft	3.0/ft	4.7/ft

Hot rolled American-made steel with an electrostatically applied powder coat surface paint. Unpainted and hot-dipped galvanized finishes available.

Black Galvanized Green Brown

